

Autotechnik 5W-30 VW

1 Litre & 5 Litre

Product Description

Bremen Autotechnik 5W/30 VW is a fully synthetic engine oil formulated to provide outstanding performance levels both in terms of engine cleanliness and fuel economy. The product is recommended for Volkswagen, Audi, Seat and Skoda engines requiring a VW specification oil and is fully compatible with exhaust after treatment devices such as diesel particulate filters.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3
API: SN/CF
BMW: LL-04
MB: 229.51
Porsche: C30
VW: 504.00 & 507.00



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PVW010	5020618201090
5 Litre	PVW050	5020618201106

Product Benefits

- * Effective environmental protection
- * Outstanding fuel efficiency
- * Excellent high & low temperature performance
- * Ensures lubricant performance over extended drain intervals

Product Usage

VAG engine types.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright and sealed in a cool dry place out of the reach of children.

Autotechnik 5W-30 VW

1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Total Base Number	ASTM D2896	mg KOH/g	7		8.33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-36	
NOACK Volatility	ASTM D5800	%		<10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			76.3
Density	ASTM D792	@ 15°C			0.85

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.