

## Autotechnik 0W-30 PSA

1 Litre & 5 Litre

### **Product Description**

Bremen Autotechnik 0W/30 PSA is a fully synthetic mid-SAPS engine oil specially formulated to meet the very latest specifications and fuel efficiency targets required by Peugeot/Citroen power units including Blue HDi and Pure Tech engine types. Suitable for use in Petrol and Diesel engines where specified.

## Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C2 PSA: B71 2312

#### **Product Benefits**

- \* Fully synthetic
- \* Reduces fuel consumption
- \* Stable lubricant film at high temperatures
- \* Suitable for extended oil drain intervals



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PSA010	5020618201212
5 Litre	PSA050	5020618201229

#### **Product Usage**

For use in engines where this viscosity and specification is required including petrol and diesel engines including those fitted with three way catalysts and diesel particulate filters

#### **Directions for Use**

Use as per the engine manufacturers recommendations

#### **Storage Instructions**

Store sealed and upright in a cool dry place out of the reach of children

#### Shelf Life

5 years from date of manufacture

Amber liquid **Appearance** 

Odour Characteristic

Insoluble in water

Revision: 2 | Date: 02/02/2023



# Autotechnik 0W-30 PSA

1 Litre & 5 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	11
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		11.5
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			61.9
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				171

## **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

## **Transport Classification**

Please see our latest EC Safety Data Sheets for details.