Autotechnik 5w-40 FS

1 Litre & 5 Litre

Revision: 1 | Date: 02/02/2023

Product Description

Bremen Autotechnik 5W/40 FS is a fully synthetic engine oil for today's high performance engines, including multi-valve, fuel injection and turbo charged petrol and diesel engines where specified.
This oil is NOT suitable for vehicles that have exhaust after treatment devices fitted.



Size	Part No	Barcode
1 Litre	PPK010	5020618201113
5 Litre	PPK050	5020618201120

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A3/B4
API: SN/CF
MB: 229.3 & 229.5
Porsche: A40
PSA: B71 2296
Renault: RN0700 & RN0710
VW: 502.00 & 505.00
BMW: LL-01

Product Benefits

* Ensures lubricant performance over extended drain intervals
* Excellent high & low temperature performance
* Outstanding fuel efficiency
* Effective environmental protection

Product Usage

For engines where this specification of lubricant is required

Directions for Use

As recommended by the engine manufacturer

Autotechnik 5w-40 FS

1 Litre & 5 Litre

Storage Instructions

Keep sealed and upright in a cool dry place out of the reach of children.

Revision: 1 | Date: 02/02/2023

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	12.5	<16.3	14.1
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	10		13
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			86.8
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				168

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.