

Autotechnik 5w-40 FS

1 Litre & 5 Litre

Revision: 1 | Date: 02/02/2023

Product Description

Bremen Autotechnik 5W/40 FS is a fully synthetic engine oil for today's high performance engines, including multi-valve, fuel injection and turbo charged petrol and diesel engines where specified.

This oil is NOT suitable for vehicles that have exhaust after treatment devices fitted.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A3/B4

API: SN/CF

MB: 229.3 & 229.5

Porsche: A40

PSA: B71 2296

Renault: RN0700 & RN0710

VW: 502.00 & 505.00

BMW: LL-01



Size	Part No	Barcode
1 Litre	PPK010	5020618201113
5 Litre	PPK050	5020618201120

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification of lubricant is required

Directions for Use

As recommended by the engine manufacturer

Autotechnik 5w-40 FS

Storage Instructions

1 Litre & 5 Litre

Keep sealed and upright in a cool dry place out of the reach of children.

Revision: 1 | Date: 02/02/2023

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	14.1
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	10		13
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			86.8
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				168

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.