

## Autotechnik 5W-40 PD

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 5W/40 PD is formulated primarily to meet the requirements of VW 505.01 for use in Pumpe Duse engines where fixed time & distance service intervals are recommended. Also suitable for a range of vehicles where a 5W/40, C3 engine oil is recommended. These vehicles include: Fiat, Alpha Romeo, Chevrolet and Lancia.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3  
API: SN/CF  
BMW: LL-04  
Fiat: 9.55535-H2 & 9.55535-S2  
Ford: WSS-M2C917-A  
GM: Dexos™ 2  
MB: 229.31 & 229.51  
Porsche: A40  
VW: 505.00 & 505.01



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PPD010	5020618201236
5 Litre	PPD050	5020618201243

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

or engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

## Autotechnik 5W-40 PD

### Storage Instructions

1 Litre &amp; 5 Litre

Store upright and sealed in a cool dry place., out of the reach of children.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	12.5	<15	13.6
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	10		11.6
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			83.8
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				166

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.