

Autotechnik 5W-30 C1

1 Litre & 5 Litre

Product Description

Bremen Autotechnik 5w/30 C1 is an advanced fully synthetic engine oil formulated from quality base oils and the most up to date additives meeting low SAPS (sulphated ash, phosphorus and sulphur) requirements. It provides excellent wear protection and is safe for use in vehicles that have a diesel particulate filter fitted. Manufactured to meet ACEA C1 specification.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C1

Ford: WSS-M2C934-B

JASO: DL-1

STJLR: .03.5005



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PC1010	5020618201137
5 Litre	PC1050	5020618201144

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Revision: 1 | Date: 02/02/2023

Autotechnik 5W-30 C1

1 Litre & 5 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	9.3	<12.5	11.4
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.6
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			67.8
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				160

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.