

## Autotechnik 5W-30 C3

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 5W/30 C3 is a fully synthetic low emission engine oil specially formulated using the very latest additive technology to produce a low SAPS lubricant. It provides excellent wear protection and is safe for use in vehicles where a diesel particulate filter is fitted.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3

API: SN/CF

BMW: LL-04

GM: Dexos™ 2

MB: 229.31, 229.51 & 229.52

VW: 505.00 & 505.01



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PC3010	5020618201038
5 Litre	PC3050	5020618201045

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

## Autotechnik 5W-30 C3

1 Litre &amp; 5 Litre

**Shelf Life**

5 years from date of manufacture.

<b>Appearance</b>	:	Amber liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Biodiesel</b>	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		8
Pour Point	ASTM D97	°C		-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			76.3
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				160

**Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

**Transport Classification**

Please see our latest EC Safety Data Sheets for details.