

Autotechnik 5W-30 C3

1 Litre & 5 Litre

Revision: 1 | Date: 02/02/2023

Product Description

Bremen Autotechnik 5W/30 C3 is a fully synthetic low emission engine oil specially formulated using the very latest additive technology to produce a low SAPS lubricant. It provides excellent wear protection and is safe for use in vehicles where a diesel particulate filter is fitted.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3
API: SN/CF
BMW: LL-04
GM: Dexos™ 2
MB: 229.31, 229.51 & 229.52
VW: 505.00 & 505.01



Size	Part No	Barcode
1 Litre	PC3010	5020618201038
5 Litre	PC3050	5020618201045

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

Autotechnik 5W-30 C3

1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture.

Revision: 1 | Date: 02/02/2023

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		8
Pour Point	ASTM D97	°C		-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			76.3
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				160

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.