

Autotechnik 5W-30 C4

1 Litre & 5 Litre

Product Description

Bremen Autotechnik 5W/30 C4 is formulated using the very latest advanced additive technology and base oils. Manufactured to meet the latest performance demands of certain Renault vehicles requiring a low SAPs (sulphated ash, phosphorous and sulphur) content. Suitable for engines with diesel particulate filters fitted where this grade and specification is required.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C4

MB: 226.51

Renault: RN0720



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PC4010	5020618201052
5 Litre	PC4050	5020618201069

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store Upright and sealed in a cool dry place, out of the reach of children.

Autotechnik 5W-30 C4

1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.4
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			74.4
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				164

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.