

## Autotechnik 5W-30 C4

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 5W/30 C4 is formulated using the very latest advanced additive technology and base oils. Manufactured to meet the latest performance demands of certain Renault vehicles requiring a low SAPs (sulphated ash, phosphorous and sulphur) content. Suitable for engines with diesel particulate filters fitted where this grade and specification is required.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C4

MB: 226.51

Renault: RN0720

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store Upright and sealed in a cool dry place, out of the reach of children.



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PC4010	5020618201052
5 Litre	PC4050	5020618201069

## Autotechnik 5W-30 C4

1 Litre &amp; 5 Litre

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.5
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			72.4
Density	ASTM D792	@ 15°C			0.85

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.