

Autotechnik 5W-30 Ford

1 Litre & 5 Litre

Product Description

Bremen Autotechnik 5W/30 Ford is an advanced fully synthetic engine oil formulated from quality base oils and the most up to date additives. It provides excellent wear protection and is safe for use in vehicles that have a diesel particulate filter fitted.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A5/B5

API: SL/CF

Ford: WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C & WSS-M2C913-D

Renault: RN0700

STJLR: .03.5003

BMW: LL-01 FE



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PFD010	5020618201076
5 Litre	PFD050	5020618201083

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store upright & sealed in a cool dry place out of the reach of children.

Autotechnik 5W-30 Ford

1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.9
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-27	
NOACK Volatility	ASTM D5800	%		13	
Total Base Number	ASTM D2896	mg KOH/g	10		12.1
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			61.9
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				169
HTHS Viscosity	ASTM D4683	mPa.s	3	3.5	

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.