

Autotechnik 5W-20 Ford

1 Litre & 5 Litre

Revision: 2 | Date: 03/02/2023

Product Description

Bremen Autotechnik 5W/20 Ford is a fully synthetic engine oil formulated for the latest intelligent Eco engines including stop/start technology. The carefully selected base stocks and synthetic additives give this multi-grade engine oil high levels of engine component protection as well as being fuel efficient.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C5

API: SN/CF

Ford: WSS-M2C948-A & WSS-M2C948-B

ILSAC: GF-5

STJLR: .03.5004



Size	Part No	Barcode
1 Litre	PFE010	5020618201175
5 Litre	PFE050	5020618201182

Product Benefits

- *Long drain service intervals, subject to manufacturers recommendations
- *Keeps engine clean
- *Protects components from wear and corrosion
- *Excellent cold start capabilities

Product Usage

For use where the engine manufacturer recommends this specification and grade of oil.

Directions for Use

As per manufacturers recommendations.

Storage Instructions

Store upright and sealed in a cool dry place out of the reach of children.

Autotechnik 5W-20 Ford

1 Litre & 5 Litre

Shelf Life

5 years from date of manufacture.

Revision: 2 | Date: 03/02/2023

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.9	<9.3	9
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	8		9.9
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		13	11
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			54
Viscosity Index	ASTM D2270				147
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-35	-39

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.