

## Autotechnik 0W-30 C2

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 0W/30 C2 is a Fully synthetic low SAPS engine oil specifically formulated to meet the requirements of the new generation Ford Dura Torq engines (2014>). This Mid SAPS formulation is also suitable for certain Alfa Romeo, Fiat, Hyundai, Jeep, Kia, Suzuki and Toyota engines.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C2

Fiat: 9.55535-DS1 & 9.55535-GS1

Ford: WSS-M2C950-A

STJLR: .03.5007



\* Image for illustrative purposes only.

### Product Benefits

- \* Especially formulated for certain Ford engines
- \* Mid SAPS formulation
- \* Excellent wear and corrosion protection
- \* Superior fuel efficiency

### Product Usage

For engines fitted with exhaust after treatment devices were this grade and specification is recommended

### Directions for Use

Use as per the vehicle manufacturers recommendations

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children

### Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Revision: 1 | Date: 03/02/2023

## Autotechnik 0W-30 C2

1 Litre &amp; 5 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		8
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			58.7
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				183

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.