Autotechnik 10W-40 SS

1 Litre & 5 Litre

Revision: 1 | Date: 03/02/2023

Product Description

Bremen Autotechnik 10W/40 SS is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and vehicles fitted with catalytic converters.



Size	Part No	Barcode
1 Litre	PSO010	5020618201014
5 Litre	PSO050	5020618201021

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A3/B4
API: SN/CF
MB: 229.1 & 229.3
Renault: RN0700 & RN0710
VW: 502.00 & 505.00

Product Benefits

* Ensures lubricant performance
* Excellent high & low temperature performance
* Outstanding fuel efficiency
* Effective environmental protection

Product Usage

For engines where this specification of lubricant is required

Directions for Use

As recommended by the engine manufacturer

Storage Instructions

Keep upright and sealed in a cool dry place out of the reach of children

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Autotechnik 10W-40 SS

1 Litre & 5 Litre

Revision: 1 | Date: 03/02/2023

Percentage of Base Oil : Less than 70%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	12.5	<16.3	13.46
Viscosity, CCS -25°c	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°c		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			81.77
Density	ASTM D792	@ 15°c			0.872
Viscosity Index	ASTM D2270				160.96

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.