

Autotechnik 0W-20 C5/C6

1 Litre & 5 Litre

Product Description

Bremen Autotechnik 0W-20 C5/C6 is a fuel efficient Mid SAPS engine oil formulated using the very latest additives and base oil technology. This product is suitable for various engine manufacturers requirements for petrol and diesel engine cars both with or without exhaust after treatment devices. Autotechnik 0W-20 C5/C6 is also used in modern small capacity engines with exhaust gas turbochargers and direct injection.

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C5 & C6 API: SP & SP-RC

BMW: LL-14 FE & LL-17 FE+

Chrysler: MS-12145

Fiat: 9.55535-DSX & 9.55535-GSX

Ford: WSS-M2C947-B1, WSS-M2C952-A1 & WSS-

M2C962-A1 ILSAC: GF-6A MB: 229.71 & 229.72 Opel: OV0401547

STJLR: .03.5006 & .51.5122 Volvo: VCC RBS0-2AE

Product Benefits

*Excellent cold start properties

*Protects engines from LSPI damage

Product Usage

Use as recommended by the vehicle manufacturer.



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PC6010	5020618201250
5 Litre	PC6050	5020618201267



Autotechnik 0W-20 C5/C6

Directions for Use

1 Litre & 5 Litre

As per the vehicle handbook

Storage Instructions

Store sealed and upright in a cool dry place

Shelf Life

5 years from date of manufacture

Appearance : Amber Liquid

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	7.8	<9.3	8.3
Viscosity, CCS -35°c	ASTM D4684	mPa.s		<6200	
Total Base Number	ASTM D2896	mg KOH/g	8		9.3
Pour Point	ASTM D97	°c		-48	
HTHS Viscosity	ASTM D4683	mPa.s	2.8	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			44.4
Density	ASTM D792	@ 15°c			0.84
Viscosity Index	ASTM D2270				165

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 14/12/2023