

## Autotechnik 0W-20 VW

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 0W-20 VW 0W/20 is a specially formulated low viscosity fully synthetic engine oil designed to match the oil test requirements of VW 508.00/509.00. It provides enhanced engine protection against component wear and is safe for use in vehicles that have Diesel Particulate Filters (DPF) and Gasoline Particulate Filters as well as Catalytic Converters. Please note - this oil is not backwards compatible to VW specifications 504.00/507.00. The oil contains a coloured dye for identification.

### Recommended for use by Bremen for the following manufacturer's specifications

Porsche: C20

VW: 508.00 & 509.00



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PVA010	5020618201281
5 Litre	PVA050	5020618201298

### Product Benefits

- \*Fully synthetic low viscosity fuel efficient engine oil
- \*Ideal for petrol and diesel engines
- \*Low Viscosity, fuel efficient

### Product Usage

For engines where this specification of lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

**Autotechnik 0W-20 VW**

1 Litre &amp; 5 Litre

**Shelf Life**

5 years from date of manufacture.

<b>Appearance</b>	:	Pale Green Liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Biodiesel</b>	:	nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7.8	<9.3	8.7
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		8.33
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			42.74
Density	ASTM D792	@ 15°C			0.841

**Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

**Transport Classification**

Please see our latest EC Safety Data Sheets for details.