Autotechnik 0W-20 VW

1 Litre & 5 Litre

Revision: 2 | Date: 18/06/2025

Product Description

Bremen Autotechnik 0W-20 VW is a specially formulated low viscosity fully synthetic engine oil designed to match the oil test requirements of VW 508.00/509.00. It provides enhanced engine protection against component wear and is safe for use in vehicles that have Diesel Particulate Filters (DPF) and Gasoline Particulate Filers as well as Catalytic Convertors.

Please note - this oil is not backwards compatible to VW specifications 504.00/507.00. The oil contains a coloured dye for identification.



Size	Part No	Barcode
1 Litre	PVA010	5020618201281
5 Litre	PVA050	5020618201298

Recommended for use by Bremen for the following manufacturer's specifications

Porsche: C20
VW: 508.00 & 509.00
FORD: M2C956-A1

Product Benefits

*Fully synthetic low viscosity fuel efficient engine oil
*Ideal for petrol and diesel engines
*Low Viscosity, fuel efficient

Product Usage

For engines where this specification of lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

Autotechnik 0W-20 VW

1 Litre & 5 Litre

Revision: 2 | Date: 18/06/2025

Shelf Life

5 years from date of manufacture.

Appearance	:	Pale Green Liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	7.8	<9.3	8.9
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		9.4
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			48.7
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				164

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.