

## Autotechnik 0W-30 VW

1 Litre & 5 Litre

Revision: 1 | Date: 28/11/2024

### Product Description

Bremen Autotechnik 0W-30 VW is the very latest generation fully synthetic low viscosity engine oil offering excellent fuel efficiency and engine protection whilst meeting the requirements of soot control for those vehicles with engine exhaust after treatment devices fitted.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3

API: SN

BMW: LL-04

MB: 229.51

Porsche: C30

VW: 503.00, 504.00, 506.00, 506.01 & 507.00



Size	Part No	Barcode
1 Litre	PVB010	5020618201373
5 Litre	PVB050	5020618201380

### Product Benefits

- \* Low SAPS formulation
- \* Fully synthetic
- \* Excellent fuel efficiency

### Product Usage

For vehicles where this grade and specification of engine oil is required.

### Directions for Use

Use as specified by the vehicle manufacturer

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children.

## Autotechnik 0W-30 VW

1 Litre &amp; 5 Litre

### Shelf Life

5 years from date of manufacture.

Revision: 1 | Date: 28/11/2024

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11.5
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		10.4
Pour Point	ASTM D97	°C		-42	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			64.2
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				175

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.