

## Autotechnik 0W-30 V

1 Litre & 5 Litre

### Product Description

Bremen Autotechnik 0W-30 V is a fully synthetic engine oil formulated to meet the performance demands of modern petrol and diesel engines. Bremen Autotechnik 0W-30 V is formulated using the very latest in base oil and additive technology, designed for extended drain performance and fuel efficiency, ideally suited for modern Volvo engines.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A5/B5

API: SL/CF

BMW: LL-01 FE

Volvo: VCC 95200377

VW: 503.00



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PVO010	5020618201335
5 Litre	PVO050	5020618201342

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification and viscosity of lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Keep upright and sealed in a cool, dry place out of the reach of children.

**Autotechnik 0W-30 V**

1 Litre &amp; 5 Litre

**Shelf Life**

5 years from date of manufacture.

<b>Appearance</b>	:	Amber liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Biodiesel</b>	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	9.3	<12.5	10.6
Total Base Number	ASTM D2896	mg KOH/g	8		12.9
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Viscosity, Kinematic 40°C	ASTM D445	mm²/s			58.9
Density	ASTM D792	@ 15°C			0.85
Pour Point	ASTM D97	°C		-40	
Viscosity Index	ASTM D2270				173

**Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

**Transport Classification**

Please see our latest EC Safety Data Sheets for details.