Autotechnik 0W-30 V

1 Litre & 5 Litre

Revision: 1 | Date: 28/11/2024

Product Description

Bremen Autotechnik 0W-30 V is a fully synthetic engine oil formulated to meet the performance demands of modern petrol and diesel engines. Bremen Autotechnik 0W-30 V is formulated using the very latest in base oil and additive technology, designed for extended drain performance and fuel efficiency, ideally suited for modern Volvo engines.



Size	Part No	Barcode
1 Litre	PVO010	5020618201335
5 Litre	PVO050	5020618201342

Recommended for use by Bremen for the following manufacturer's specifications

ACEA: A5/B5
API: SL/CF
BMW: LL-01 FE
Volvo: VCC 95200377
VW: 503.00

Product Benefits

* Ensures lubricant performance over extended drain intervals
* Excellent high & low temperature performance
* Outstanding fuel efficiency
* Effective environmental protection

Product Usage

For engines where this specification and viscosity of lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep upright and sealed in a cool, dry place out of the reach of children.

Autotechnik 0W-30 V

1 Litre & 5 Litre

Revision: 1 | Date: 28/11/2024

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	10.6
Total Base Number	ASTM D2896	mg KOH/g	8		12.9
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			58.9
Density	ASTM D792	@ 15°c			0.85
Pour Point	ASTM D97	°c		-40	
Viscosity Index	ASTM D2270				173

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.