

# Autotechnik 5W-30 ST

1 Litre & 5 Litre

## **Product Description**

Technolube 5W-30 ST is a fully Synthetic engine oil specially formulated for certain Stellantis group DV5R & EB2 engine types. The product helps prevent occurrences of LSPI (Low Speed Pre-Ignition) whilst offering excellent engine protection and emission control.

Please check which oil is recommended for the engine type prior to use.

# Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3 API: SN Plus GM: Dexos™ 2

MB: 229.31, 229.51 & 229.52 Stellantis: FPW9.55535/03 PSA: B71 2290 & B71 2297



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	PCLS010	5020618201397
5 Litre	PCLS050	5020618201403

#### **Product Benefits**

- \* Excellent Engine Protection
- \* Reduces occurrences of LSPI
- \* Outstanding emission Control

#### **Product Usage**

Use as per engine manufacturers recommendations

#### **Directions for Use**

As per the vehicle handbook

#### **Storage Instructions**

Store sealed and upright in a cool dry place out of the reach of children



# Autotechnik 5W-30 ST

**Shelf Life** 

1 Litre & 5 Litre

5 years from date of manufacture

Appearance : Amber Liquid

Odour : Chracteristic

Solubility : Insoluble in Water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	11	12.5	12.2
Density	ASTM D792	@ 15°c			0.85
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		9.5
Pour Point	ASTM D97	°c	-36		
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		9	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s	65		72.9
Viscosity Index	ASTM D2270				166

### **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

## **Transport Classification**

Please see our latest EC Safety Data Sheets for details.