

## Autotechnik 5W-30 ST

1 Litre & 5 Litre

Revision: 1 | Date: 08/09/2025

### Product Description

Technolube 5W-30 ST is a fully Synthetic engine oil specially formulated for certain Stellantis group DV5R & EB2 engine types. The product helps prevent occurrences of LSPI ( Low Speed Pre-Ignition) whilst offering excellent engine protection and emission control.

Please check which oil is recommended for the engine type prior to use.

### Recommended for use by Bremen for the following manufacturer's specifications

ACEA: C3

API: SN Plus

GM: Dexos™ 2

MB: 229.31, 229.51 & 229.52

Stellantis: FPW9.55535/03 (V1)

PSA: B71 2290 & B71 2297



Size	Part No	Barcode
1 Litre	PCLS010	5020618201397
5 Litre	PCLS050	5020618201403

### Product Benefits

- \* Excellent Engine Protection
- \* Reduces occurrences of LSPI
- \* Outstanding emission Control

### Product Usage

Use as per engine manufacturers recommendations

### Directions for Use

As per the vehicle handbook

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children

## Autotechnik 5W-30 ST

1 Litre &amp; 5 Litre

### Shelf Life

5 years from date of manufacture

Revision: 1 | Date: 08/09/2025

Appearance	:	Amber Liquid
Odour	:	Chracteristic
Solubility	:	Insoluble in Water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	11	12.5	12.2
Density	ASTM D792	@ 15°C			0.85
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		9.5
Pour Point	ASTM D97	°C	-36		
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		9	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	65		72.9
Viscosity Index	ASTM D2270				166

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.